

## MA-DBO-3MIMO

### 2.3-2.7 GHz & 4.9-6 GHz Omni Dual Band MIMO Applications Antenna

MARS Dual Band MIMO Omni antenna provides coverage of 2.3 to 2.7 GHz & 4.9 to 6 GHz in a single antenna radome.



## Specifications

### *Electrical*

Frequency range	2.3-2.7 GHz & 4.9-6GHz
GAIN, typ.	2.3-2.7 GHz @ 3 x 4 dBi 4.9-6 GHz @ 3 x 7 dBi
VSWR, max.	2 : 1
Polarization	Linear, Vertical
3dB Beam-Width, H-Plane, typ.	Omni Directional
Port to Port Isolation.typ	-20 dB
Input power, max.	20 Watt
Input Impedance	50 Ohm

### *Mechanical*

Dimensions (DxH)	205 x 330 mm (8.07" x 13")
Connector	3 x N-Type Female
Weight	1.5 Kg.
Back Plane	Aluminium; protected through chemical passivation
Radome	UV Protected Plastic
Mount	Pole Mount

### *Environmental*

Operating Temperature Range	-40°C to +70°C
Vibration	According to IEC 60721-3-4
Flammability	UL94
Water Proofing	IP-65
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com