

MA-IS91-DS10

902-928 MHz Subscriber Antenna

MARS 915 MHz Antenna is designed for Point-to-Multipoint systems using the ISM 915 MHz band.

Additional features:

- High efficiency.
- Superb co-siting performance due to high cross pol rejection.
- Unobtrusive, blends easily with the environment.
- Optionally available with Pole Mount or MNT-22 (pole/wall, azimuth and elevation adjustable mount).



Specifications

<i>Electrical</i>	
Frequency range	902-928 MHz
Gain	10.5 ± 0.5 dBi
VSWR, max.	1.7: 1
Polarization	Dual Slant ±45°
3dB Beam-Width, H-Plane, typ.	46°
3dB Beam-Width, E-Plane, typ.	46°
Side Lobes, min.	-16 dB
Port to Port Isolation, typ.	-30 dB
Front to Back Ratio, min.	-16 dB
Input power, max.	20 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded
<i>Mechanical</i>	
Dimensions (HxWxD)	370 x 370 x 40 mm (14.5" x 14.5" x 1.6")
Connector	2 x N-Type
Weight	2 kg.
Mounting	See ordering options
Radome	UV Protected Polycarbonate
Back Plane	Aluminum protected through chemical passivation.
<i>Environmental</i>	
Operating Temperature Range	-55°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 Km/h (Survival)
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4, EN 302 085 (Annex A.1.1)
Salt Fog	According to IEC 68-2-11

Ordering Options

MA-IS91-DS10	Antenna Suited for MNT-22
MA-IS91-DS10B	Antenna with MNT-22 mount

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com