

MA-WA36-DP11

3.3-4.01 GHz Dual Polarization Antenna

MARS 3.6 GHz Dual Polarized Antenna is a wide band antenna designed for LTE, Wi-Fi, LAN, MMDS, WLL and WiMAX applications.

Additional Features:

- Exceptionally efficient performance.
- High gain/size ratio.
- Aesthetic design.
- Weatherized and durable.



Specifications

Electrical

Frequency range	3.3-4.01 GHz
Gain, typ.	11 dBi
VSWR, max.	1.7 : 1
Polarization	Dual Pole
	Linear, Vertical & Horizontal (Diamond shape)
3dB Beam-Width, Azimuth, typ.	60°
3dB Beam-Width, Elevation, typ.	40°
Port to Port Isolation, min	-25 dB
Side Lobes, min.	-10 dB
Front to Back Ratio, min.	-17.5 dB
Input power, max.	50 Watt
Input Impedance	50 Ohm

Mechanical

Dimensions (HxWxD)	112 x 112 x 33.5 mm (4.41" x 4.41" x 1.32")
Connector	2 x Right Angle SMA, Female
Weight	147 gr.
Mounting	See Ordering Options
Radome	UV Protected Polycarbonate
Back Plane	Aluminum protected through chemical passivation.

Environmental

Operating Temperature Range	-55°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 Km/h (Survival)
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4, EN 302 085 (Annex A.1.1)
Salt Fog	According to IEC 68-2-11

Ordering Options

MA-WA36-DP11	Antenna 2 x Right Angle SMA ,Female connectors Suited for MNT-4LU mount
MA-WA36-DP11B	Antenna 2 x Right Angle SMA ,Female connectors with MNT-4LU mount

Patterns are available on our website

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com