

MA-WA692755-TBDP14

698-960 MHz & 1695-2700 MHz & 5150-5925 MHz Stadium Dual Pol Directional Antenna

MARS new **Triple BAND, DUAL POL** antenna is designed especially for **arenas and stadiums** that have to supply high capacity and reliable wireless data.

The MARS MA-WA692755-TBDP14 provides solutions for services such as LTE, Cellular (2G, 2.5G and 3G), Wi-Fi and WiMAX applications.

The antenna is PIM certified, thus making it suitable for all multi-carrier systems.

Additional Features:

- Efficient and stable performance with 12-14 dBi of gain
- UV protected radome suitable for harsh environment installations
- Durable construction and weather resistant
- Easy mounting allowing Az/EI adjustment
- Aesthetic design
- Wind load up to 200 km/h



Available in iBwave database

Specially designed for Arenas and Stadiums

Specifications

Electrical

Frequency range		698-960 MHz	1695-2700 MHz	5150-5925 MHz
Gain, typ.	V-pol	12 dBi	13 dBi	14 dBi
	H-pol	13 dBi	13 dBi	14 dBi
VSWR, max.		2.0 : 1	2.0 : 1	2.0 : 1
Polarization	Dual Pol	Vertical & Horizontal		
Port to Port Isolation, min.		-22 dB	-37 dB	-24 dB
3dB Beam-Width, Azimuth, typ.		35°	35°	35°
3dB Beam-Width, Elevation, typ.		35°	35°	35°
Front to Back Ratio, min.		-22 dB		
PIM, 3 rd order, 2X20W		-150 dBc		
Input power, max.		50 Watt		
Impedance		50 Ohm		

Mechanical

Dimensions (HxWxD)	800 x 600 x 110 mm
Connector	See Ordering Options
Weight	~ 6.1 kg
Mounting	See ordering options
Radome	UV Protected Plastic
Back Plane	Aluminum protected through chemical passivation.

Environmental

Operating Temperature Range	-55°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 Km/h (Survival)
Flammability	UL94
Water Proofing	IP-65
Humidity	ETS 300 019-1-4, EN 302 085 (Annex A.1.1)
Salt Fog	According to IEC 68-2-11

Ordering Options

MA-WA692755-TBDP14	Antenna 4 x N-Type Female connectors (2 x 698-960 MHz & 1695-2700 MHz and 2 x 5150-5925 MHz) Suited for MNT-25 mount
MA-WA692755-TBDP14DIN	Antenna 4 x 4.3-10 Female connectors (2 x 698-960 MHz & 1695-2700 MHz and 2 x 5150-5925 MHz) Suited for MNT-25 mount
MA-WA692755-TBDP14B	Antenna 4 x N-Type Female connectors (2 x 698-960 MHz & 1695-2700 MHz and 2 x 5150-5925 MHz) with MNT-25 mount
MA-WA692755-TBDP14DINB	Antenna 4 x 4.3-10 Female connectors (2 x 698-960 MHz & 1695-2700 MHz and 2 x 5150-5925 MHz) with MNT-25 mount

Mars Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com