

## MA-WC25-2DS17

### 2.3-2.7 GHz 2 x Dual Slant Base Station Antenna, 65°

MARS MA-WC25-2DS17 is a DOUBLE Dual Slant (4X4) Base Station Antenna 65°

MA-WC25-2DS17 features:

- Efficient and stable performance with 17dBi of gain.
- Full 2.3-2.7 GHz band coverage.
- UV protected radome suitable for harsh environment installations.



## Specifications

### Electrical

Frequency range	2.3-2.7 GHz
GAIN, typ.	4 x 17 dBi
VSWR, max.	1.7 : 1
Polarization	2 x Dual Slant $\pm 45^\circ$
3 dB Beam-Width, H-Plane, typ.	65°
3 dB Beam-Width, E-Plane, typ.	8°
Side Lobes, typ.	-12 dB
Port to Port Isolation, min.	-27 dB
Front to Back Ratio, typ.	-30 dB
Input power, max.	50 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded

### Mechanical

Dimensions (HxWxD)	812 X 470 X 70 mm (31.9" X 18.5" X 2.7")
Weight	5 kg.
Connector	4 x N-Type, Female
Back Plane	Aluminum protected through chemical passivation
Radome	UV Protected Plastic
Mount	MNT-25

### Environmental

Operating Temperature Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-65
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Salt Fog	According to IEC 68-2-11
Ice and Snow	25mm radial (survival)

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com