

MA-WC36-17

3.3-3.8 GHz Sector Antenna for LTE & WiMAX Applications, 70°

MARS 70° Base Station Antenna is light-weight yet has a robust and durable construction.

Additional Features:

- Specially designed for LTE & WiMAX applications.
- Quick and easy installation.
- Easy mounting allowing obtaining required down tilt.
- Suitable for harsh environment installations.
- DC grounded.

Applications:

- Licensed band applications.
- Point-to-Multi Point Applications.
- WLL applications.



Specifications

Electrical

Frequency range	3.3-3.8 GHz
GAIN, typ.	16.5 dBi
VSWR, max.	1.7 : 1
Polarization	Linear, Vertical
3 dB Beam-Width, H-Plane, typ.	70°
3 dB Beam-Width, E-Plane, typ.	9°
Side Lobes, min.	ETSI EN 302 085 V1.2.3-CS1
Cross Polarization, min.	ETSI EN 302 085 V1.2.3-CS1
Front to Back Ratio, min.	ETSI EN 302 085 V1.2.3-CS1
Input power, max	50 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded

Mechanical

Dimensions (HxWxD)	573 x 95 x 53 mm (22.6" x 3.7" x 2.1")
Weight	700 gr.
Connector	N-Type, Female
Back Plane	Aluminum; protected through chemical passivation
Radome	UV Protected Polycarbonate
Mount	See ordering options

Environmental

Operating Temperature Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Salt Fog	According to IEC 68-2-11
Ice and Snow	25mm radial (survival)

Standard Compliance

ETSI EN 302 085 V1.2.3 – CS1

Ordering Options

MA-WC36-17	Antenna Suited for MNT-22 (optional wall/pole adjustable mount)
MA-WC36-17B	Antenna with MNT-22 mount

Patterns are available on our website

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com