

MA-WD2455-DS18

2.3 – 2.7 GHz & 5.1 – 5.9 GHz, 4X4 Dual Band, Dual-Slant Base Station Antenna, 90°

MARS MA-WD2455-DS18 is a 4X4 (MIMO) high gain antenna with Dual band, Dual Slant antenna provides coverage of 2.3-2.7 GHz frequency band and 5.1-5.9 GHz frequency band in a single antenna radome.

Additional Features:

- Designed to meet WAVE2, 802.11ac & more.
- Easy mounting allowing Az/EI adjustment.



Specifications

Electrical

Frequency range	2.3-2.7 GHz	5.1-5.9 GHz
Gain, typ.	16 dBi	18 dBi
VSWR, max.	2.0 : 1	
Polarization, Dual-Slant	±45°	±45°
3 dB Beam-Width, Azimuth, typ.	90°	90°
3 dB Beam-Width, Elevation, typ.	8°	4°
Side Lobes, min.	-10 dB	
Cross Polarization, typ.	-15 dB	
Front to Back Ratio, min.	-32 dB	
Port to Port Isolation, min.	Intra-band -17 dB	Inter-band -30 dB
Input power, max	50 Watt	
Input Impedance	50 Ohm	
Lightning Protection	DC Grounded	

Mechanical

Dimensions (HxWxD)	807 x 464 x 50 mm (31.77" x 18.27" x 1.97")
Weight	3 Kg.
Connector	4 x N-Type, Female
Back Plane	Aluminum protected through chemical passivation
Radome	UV Protected Plastic
Mount	MNT-25

Environmental

Operating Temperature Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-65
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Salt Fog	According to IEC 68-2-11

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com