



## **MA-WE90-7X**

## 915 MHz Base Station Antenna, 120°

MARS 915 MHz Base Station Antenna provides a robust and efficient solution for the Point-to-Multipoint systems based on the ISM 915 MHz band. Additional Features:

- 120° azimuthal coverage.
- Suitable for harsh environment installations.
- DC grounded.
- Easy mounting allows to obtain required down tilt degree with the optional MNT-25 mount.

## **Specifications**

Electrical	
Frequency range	902-928 MHz
GAIN, min.	11.5 dBi
VSWR, max.	1.7 : 1
Polarization	Linear, Vertical
3 dB Beam-Width, Horizontal Plane, typ.	120°
3 dB Beam-Width, Elevation Plane, typ.	15°
Side Lobes, min.	-11 dB
Cross Polarization, min.	-15 dB
Front to Back Ratio, min.	-18 dB
Input power, max.	50 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded
Mechanical	
Dimensions (HxWxD)	1208 x 328 x 183 mm (47.56" x 12.91" x 7.20")
Weight	4.5 kg.
Connector	N-Type, Female
Back Plane	Aluminum; protected through chemical passivation
Radome	UV Protected, Plastic
Mount	See ordering options
Environmental	
Operating Temperature Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-65
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Salt Fog	According to IEC 68-2-11
Ice and Snow	25mm radial (survival)

Ordering Options	
MA-WE90-7X	Antenna Suited for MNT-25 (optional tilt mount)
MA-WE90-7XB	Antenna with MNT-25 mount

## Patterns are available on our website

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.