

## MA-WO8622-DB2

### 790-960 MHz & 1695-2700 MHz Dual Band OMNI Antenna

MARS Dual Band OMNI antenna provides coverage 790-960 MHz & 1695-2700 MHz in a single antenna radome.

Additional Features:

- Simultaneous coverage of LTE & 802.11 a, b, e, g, n,
- Light weight and durable construction.
- UV protected radome.
- Indoor and Outdoor use
- Low PIM



Available in iBwave database

## Specifications

### Electrical

Frequency range	790-960 MHz & 1695-2700 MHz
GAIN, typ.	2 dBi @ 790-960 MHz 2.5-5.8 dBi @ 1695-2700 MHz
VSWR	< 2 : 1 @ 810-945MHz & 1695-2700 MHz ; <2.5:1 @ 790-960 MHz
Polarization	Linear Vertical
Horizontal Beam width	360° Omnidirectional
Vertical Beam width	70° @790-960 MHz ; 70°-30° @ 1695-2700 MHz
Passive Intermodulation(2x20W)	<-150 dBc
Input power, max.	20 Watt
Input Impedance	50 Ohm

### Mechanical

Dimensions (HxD)	192 x 30 mm (7.5" x 1.2")
Connector	N-Type Female
Weight	95 gr.
Radom	UV Protected Plastic
Mount	One hole mounting (16 mm diameter) to surfaces of max. 6mm thickness

### Environmental

Operating Temperature Range	-40°C to +70°C
Vibration	According to IEC 60721-3-4
Water Proofing	IP-67
Flammability	UL94
Wind Load	6N/at 150 Km/h
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com