

MR-PBCT55-A

CDMA Bi - Directional Amplifier /Repeater/

Gain Automatic Control Personal BDA provides a cost effective solution for enhancing radio communication in offices and other small area spaces. Amplifier features small size and is easy to install.



Specifications

Electrical

	Down Link	Up Link
Frequency range	869-894 MHz	824-849 MHz
Operational Frequency Band, MHz (Other Available on Request)	869-879 MHz	824-834 MHz
Gain at, min. Attenuation	55 dB	
Pass Band Ripple	±2 dB	
Output Power @ 1 dB Compression	18 dBm	
Output IP3, min.	28 dBm	
Noise Figure max.	6.5 dB	
ALC	8 dBm	
RF Output Power Range	20 dB	
Impedance	50 Ohm	
VSWR, max.	2 : 1	
Input Power, max.	-20 dBm	
Biassing (Through Separate DC Connector)	6V / 400mA (Adaptor MR-PS13 should be Ordered Separately)	

Mechanical

Dimensions	120 x 70 x 35 mm
Weight	200 gr.
Connectors	SMA, Female
Housing	Aluminum, Anodized, Black
Mount	Wall / Ceiling Mounting

Environmental

Operating Temperature Range	-10°C to +50°C
Humidity, min.	95%

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com