

MR-PD04-X1

4 Way Splitter

Professional high performance 4 Way Splitter.

Additional Features:

- Bi-directional splitter.
- Reliable and stable performance.
- Easy installation.



Specifications

Electrical

Operating Frequency range	2.3-2.6 GHz
Insertion Loss, max.	0.7 dB
Input/Output VSWR	1.5 Max
Amplitude Balance, max.	0.5 dB
Phase Unbalance, max.	7°
Isolation, min.	20 dB
Impedance	50 Ohm
Power rating, load VSWR better then 1.5:1	20 Watt

Mechanical

Dimensions (L x W x H)	197 x 136 x 82 [excluding mount]
Weight:	Less than 1.1 kg.
Number of Outputs	4
Connectors	N-Type, Female
Mounting	Mast

Environmental

Operating Temperature Range	-40°C to +70°C
Humidity, min.	95%
Splash, Dust	Protected

Mars Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 58861, P.O.Box 5 AZOR 58008, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com