

## MA-DBO2455-3

### 2.3-2.7 GHz & 4.9-6.4 GHz Dual Band Omni Antenna

MARS Dual Band Omni antenna provides coverage of 2.3 to 2.7 GHz & 4.9 to 6.4 GHz in a single antenna radome.

Additional Features:

- Simultaneous coverage of LTE, 802.11 a, b, g, WiMAX & 4.9 GHz Public Safety bands.
- Light weight and durable construction.
- UV protected radome made of polycarbonate.
- Suitable for either outdoor (car top) or indoor (ceiling) installations.\*



### Specifications

#### Electrical

Frequency range	2.3-2.7 GHz & 4.9-6.4 GHz
GAIN, typ.	2.3-2.7 GHz @ 2 dBi (on 20+ cm diameter ground plane) ** 4.9-6.4 GHz @ 4 dBi (on 20+ cm diameter ground plane) **
VSWR	2: 1 (max.); 1.5 : 1 (typ.)
Polarization	Linear Vertical
Input power, max.	20 Watt
Input Impedance	50 Ohm

#### Mechanical

Dimensions (H x Dia.)	34 x 54 mm (1.3" x 2.1")
Connector	N-Type Female (Bottom)
Weight	60 gr.
Back Plane	Aluminum; protected through chemical passivation
Radome	UV Protected Polycarbonate
Mount	Fixed Roof Top Mounting

#### Environmental

Operating Temperature Range	-40°C to +70°C
Vibration	According to IEC 60721-3-4
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)

(\*) Supplied with 78 mm disc for ceiling installation.

(\*\*) Gain without ground plane is:

- 0 dBi @ 2.3-2.7 GHz
- 2 dBi @ 4.9-6.1 GHz

Patterns are available on our website

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com