

## MA-WO440-5

### 406-470 MHz OMNI Directional Antenna

MARS MA-WO440-5 is an OMNI Directional Antenna covering 406-470 MHz suitable for TETRA application, providing a stable and efficient performance with 5dBi of gain.

Additional Features:

- Cost effective solutions for utilities and emergency services.
- UV Protected radome suitable for harsh environment installation.



### Specifications

#### **Electrical**

Frequency Range,	406-470 MHz
GAIN, typ.	5 dBi
VSWR, max.	2 : 1
Polarization	Linear, Vertical
3 dB Beam-Width, H-Plane, typ.	OMNI – Directional 360°
3 dB Beam-Width, E-Plane, typ.	40°
Down Tilt, typ.	10°
Input power, max.	50 Watt
Anti Static Protection	DC Grounded
Input Impedance	50 Ohm

#### **Mechanical**

Dimensions (HxDia.)	900 x 60 mm (35.4" x 2.36")
Weight	600 gr.
Connector	N-Type, Female
Radome	UV Protected Plastic
Mounting Brackets/Clamps	Aluminum Protected Through Chemical Passivation

#### **Environmental**

Operating Temperature Range	-30°C to + 70°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-65
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com