

## MA-WO3860-MIMO

### 380-6000 MHz Ultra Wide Band MIMO Omni Antenna

MARS MIMO Omni Antenna provides coverage of 380-6000 MHz in a single radome antenna 4G, 3G, 2.5G and 2G cellular, as well as ISM, WLAN, UNII, Bluetooth, Wi-Fi, WMTS IMT-MC450 , TVWS, LTE and CBRS. OnGo Certified Systems.

The MIMO Omni Antenna is easily installed either on ceilings or a 2" Pole Mount and is highly recommended as an outstanding antenna solution for in building or outdoor installations.

Additional Features include:

- Low/mid gain
- UV protected radome
- Low profile



### Specifications

#### Electrical

Frequency Range	380-6000 MHz
GAIN, typ	Port 1 & 2 1-5 dBi @ 380-1200 MHz 6 dBi @ 1200-1900 MHz 7 dBi @ 1900-3300 MHz 8dBi @ 3300-6000 MHz
VSWR, max.	1.5:1 typ; 2.5: 1 max.
Polarization	Linear, Vertical
Input power, max	50 Watt
3 dB Beam Width H-Plane	Omni directional
Port to Port Isolation	5-40 dB (across the frequency band)
Input Impedance	50 Ohm
PIM, 3rd order, 2X20W	-150 dBc

#### Environmental

Antenna dimension (L x W x H)	295 x 125 x 147 mm (11.6" x 4.92" x 5.78")
Weight	300 gr.
Connector	2x N-Type Female or 4.3-10 optionally
Back Plane	Aluminum, protected through chemical passivation
Radome	UV Protected Plastic
Mounting	Ceiling/2"Pole or Wall mount optionally

#### Environmental

Operating Temperature Range	-40°C to +65°C
Wind Load	200 Km/h (Survival)
Vibration	According to IEC 60721-3-4
Water Proofing	IP-67 (for outdoor use only)
Flammability	UL94
Salt Fog	According to IEC 68-2-11
Humidity	ETS 300 019-1-4, EN 302 085 (Annex A.1.1)

### Ordering Options

MA-WO3860-MIMO	Antenna for Indoor with 2 x N-Type Female connector and Ceiling mount
MA-WO3860-MIMO-N	Antenna for Indoor with 2 x 4.3-10 Female connector and Ceiling mount
MA-WO3860-MIMO-R	Antenna for Outdoor with 2 x N-Type Female connector and 2" Pole/Wall mount
MA-WO3860-MIMO-NR	Antenna for Outdoor with 2 x 4.3-10 Female connector and 2" Pole/Wall mount
MA-WO3860-MIMO-NA	2 x 12" Coaxial Plenum Rated Pigtail with 4.3-10, Female Connector and Ceiling Mount
MA-WO3860-MIMO-A	2 x 12" Coaxial Plenum Rated Pigtail with N-Type, Female Connector and Ceiling Mount

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor St. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: info@marsant.co.il • web: www.mars-antennas.com