







## **MA-WO4760-SISO**

## 470-6000 MHz Wide Band SISO Omni Antenna

MARS SISO Omni Antenna provides coverage of 470-6000 MHz in a single antenna radome. 4G, 3G, 2.5G and 2G cellular, as well as ISM, WLAN, UNII, Bluetooth, Wi-Fi, WMTS IMT-MC450, TVWS,LTE and CBRS. OnGo Certified Systems.

The SISO Omni Antenna is easy-installed on ceiling or 2" Pole Mount and is highly recommended as an outstanding logistic solution for In-Building and outdoor installations and applications.

Additional Features:

- · Low/mid gain.
- UV protected radome made of polycarbonate.
- Low profile.



## **Specifications**

_		
-	ectric	2 I

Frequency Range	470-6000 MHz
GAIN, typ	0.5-5 dBi @ 470-1200 MHz 6 dBi @ 1200-1900 MHz 7 dBi @ 1900-3300 MHz 8dBi @ 3300-6000 MHz
VSWR	3:1 max.@470-510 MHz ; < 2.2:1 @500-6000 MHz
Polarization	Linear, Vertical
Input power, max	50 Watt
3 dB Beam Width-Plane	Omni directional
Input Impedance	50 Ohm
PIM, 3rd order, 2X20W	-150 dBc

Antenna dimension (D x H)	120 x 146 mm (4.72" x 5.78")		
Weight	150 gr.		
Connector	See Ordering Option		
Back Plane	Aluminum, protected through chemical passivation		
Radome	UV Protected Polycarbonate		
Mounting	See Ordering Option		
Environmental			

211111 Offitter				
Operating Temperature Range	-40°C to +65°C			
Wind Load	200 Km/h (Survival)			
Vibration	According to IEC 60721-3-4			
Water Proofing	IP-67 (for outdoor use only)			
Flammability	UL94			
Salt Fog	According to IEC 68-2-11			
Humidity	ETS 300 019-1-4, EN 302 085 (Annex A.1.1)			

Ordering Options	
MA-WO4760-SISO	Antenna for Indoor with N-Type Female connector and Ceiling mount
MA-WO4760-SISO-N	Antenna for Indoor with 4.3-10 Female connector and Ceiling mount
MA-WO4760-SISO-R	Antenna for Outdoor with N-Type Female connector and 2" Pole/Wall mount
MA-WO4760-SISO-NR	Antenna for Outdoor with 4.3-10 Female connector and 2" Pole/Wall mount
MA-WO4760-SISO-NA	12" Coaxial Plenum Rated Pigtail with 4.3-10, Female Connector and

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.