

MA-WE12-DP11

1.2-1.45 GHz Dual Polarization Base Station Antenna, 120°

MARS 120° Dual Polarization Base Station Antenna with 10±1 dBi of gain is lightweight yet has a robust and durable construction.

Antenna Features:

- Quick and easy installation.
- Aesthetic and unobtrusive radome.
- Easily adapted to any RF connector.
- Easy mounting allowing obtaining required down tilt degree.

Applicable Applications:

- Point-to-Multi-Point Systems
- For WLL applications
- MMDS
- ISM applications



Specifications

Electrical

Frequency range	1.2-1.45 GHz
GAIN,	10±1dBi
VSWR, max.	2 : 1
Polarization	Dual Pole
	Linear, Vertical and Horizontal
3 dB Beam-Width, Azimuth, typ.	120°
3 dB Beam-Width, Elevation, typ.	20°
Side Lobes, min.	-10 dB
Port to Port Isolation, min.	-30 dB
Front to Back Ratio, min.	-24 dB
Input power, max.	50 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded

Mechanical

Dimensions (HxWxD)	1446x 248 x 113 mm (56.9" x 9.7" x 4.5")
Weight	4.6 kg.
Connector	2 x N-Type, Female
Back Plane	Aluminum protected through chemical passivation
Radome	UV Protected, Plastic
Mount	MNT-25

Environmental

Operating Temperature Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-65
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Salt Fog	According to IEC 68-2-11

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com