





## **MA-WO11-5**

## 1 -1.4 GHz Vertical Omni Directional Antenna

MARS MA-WO11-5 is an Vertical OMNI Directional Antenna covering from 1GHz up to 1.4 GHz in a single antenna radome. Perfect matching with any additional ground plane. Pattern: Omni Directional with any elevation up tilted in the frequency band.



## **Specifications**

	-	-	
_		ric	-
 _			~

=: · · · · · · · · · · · · · · · ·		
Frequency Range	1.0 -1.4 GHz	
GAIN, typ.	5 dBi	
VSWR, max.	2:1	
Polarization	Vertical	
3 dB Beam-Width, Azimuth, typ.	360°	
3 dB Beam-Width, Elevation, typ.	30°	
Input power, max.	50 Watt	
Lightning Protection	DC Grounded	
Input Impedance	50 Ohm	
Mechanical		
Dimensions (H x D.)	516 x 76 mm	
Base Dimensions (H x D)	5 x 130 mm	
Weight	1.2 Kg	
Connector	N-Type, Female	
Base	Aluminum protected through chemical passivation	
Radome	UV Protected Plastic	
Mounting	6 holes on base	

## **Environmental**

Operating Temperature Range	-40°C to +70°C
Vibration	According to IEC 60721-3-4
Wind Load	200 Km/h (Survival)
Flammability	UL94
Water Proofing	IP-65
Humidity	ETS 300 019-1-4,EN 302 085 (Annex A.1.1)
Salt Fog	According to IEC 68-2-11

Mars Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.