

MA-WD78-DP17

7.125 – 8.5 GHz Dual Polarization Base Station Antenna, 90°

Mars 7.125- 8.5 GHz Dual Polarized Base Station Antenna designed to provide full coverage for the 7.5 GHz frequency band. Suitable for special uses.

Additional Features:

- Efficient and stable performance.
- High gain/size ratio.
- Lightweight and durable construction.

UV protected radome made of polycarbonate suitable for harsh weather environment.



Specifications

Electrical

Frequency range	7.125 – 8.5 GHz
Gain, typ.	16.5 dBi
VSWR, max.	1.7 : 1 typ, 2 : 1 max
Polarization	Dual Pole Linear, Vertical & Horizontal
3dB Beam-Width, Azimuth, typ.	90°
3dB Beam-Width, Elevation, typ.	6°
Side Lobes, typ.	-10 dB
Cross Polarization, typ.	-18 dB
Front to Back Ratio, min.	-30 dB
Port to Port Isolation, min.	-30 dB
Input power, max.	10 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded

Mechanical

Dimensions (HxWxD)	370 x 370 x 40 mm (14.5"x 14.5"x1.6")
Connector	2 x N-type
Weight	2 Kg
Mounting	MNT-22
Radome	UV Protected Polycarbonate
Back Plane	Aluminum protected through chemical passivation.

Environmental

Operating Temperature Range	-55°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 Km/h (Survival)
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4, EN 302 085 (Annex A.1.1)
Salt Fog	According to IEC 68-2-11

Mars Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 58861, P.O.Box 5 AZOR 58008, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com