

MA-CL92-5

Dual Band – Quasi-Omni Panel Antenna

Dual Band antenna can be used for DAS applications and covers GSM 900, ISM and WLAN bands.

Features:

- Aesthetic, small size design with unobtrusive profile that blends easily with any environment.
- Can be used for either Indoor or Outdoor applications.



Specifications

Electrical

Standard	900 MHz	2.4 GHz
Frequency range	902 – 928 MHz	2.4 – 2.5 GHz
GAIN, typ.	5 dBi	5 dBi
VSWR, max.	1.8 : 1	1.6 : 1
3 dB Beam-Width, H-Plane, typ.	120°	110°
3 dB Beam-Width, E-Plane, typ.	65°	70°
Polarization	Mixed, Vertical and Horizontal	
Front to Back, min	9 dB	
Input power, max	5 Watt	
Input Impedance	50 Ohm	
Lightning Protection	DC Grounded	

Mechanical

Dimensions (LxWxH)	230 x 214 x 31 mm (9.1"x8.4"x1.2")
Weight	Approx 500 gr.
Connector	N-Type, Female
Back Plane	Aluminum; protected through chemical passivation
Radome	UV Protected Polycarbonate
Mount	See Ordering Options

Environmental

Operating Temperature Range	- 40°C to + 65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-65
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Salt Fog	According to IEC 68-2-11
Service Life	>10 years

Ordering Options

Model No.	Application & Mount
MA-CL92-5	Indoor/Outdoor Antenna, Wall Mountable
MA-CL92-5R	Outdoor Antenna, suited for MNT-22 Az/EI adjustable mount
MA-CL92-5RB	Outdoor Antenna, equipped with MNT-22 Az/EI adjustable mount

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com